

GALAXY PIN™



Pin Perf Panels with ClimaPlus Performance/ DONN DX/DXL Suspension System

FEATURES AND BENEFITS

- Random, fine and coarse perforations
- Economical, all-purpose ceiling pattern available in various panel sizes and edge details.

APPLICATIONS

- Retail or Department stores
- Offices
- Corridors
- Retail store

SUBSTRATE

- Water-felted mineral fiber

Perforated-textured panel



Edge	Panel Size ³	Class	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹
SQ	2 x 2 x 1/2" 600 x 600 x 12mm	Class A	10112 ME 10112	-	30	.88	White	A	Low		45%
	2 x 2 x 5/9" 600 x 600 x 14mm	Class A	10114 ME 10114	.50	30	.88	White	A, B, C	Low		45%
	2 x 4 x 5/9" 600 x 1200 x 14mm	Class A	10314 ME 10314	.50	33	.88	White	A, B, C	Low		45%
SLT	2 x 2 x 5/9" 600 x 600 x 14mm	Class A	10124 ME 10124	.50	33	.88	White	D	Low		45%
	2 x 4 x 5/9" 600 x 1200 x 14mm	Class A	10324 ME 10324	.50	33	.88	White	D	Low		45%

LEGEND

Low Emission (VOC Class) >.85LR

Meets the emission test criteria as low-emitting prescribed by the Singapore Green Building Council (SGBC) following ASTM D5116-06 testing methods

GRID PROFILE OPTIONS

A DX® DXI DXII DXIII	B Centricitee™ DXT™	C Omega™ DXM™	D DX® DXI DXII DXIII	E Centricitee™ DXT™	F Fineline® 1/8" DXFF™	G Fineline® 1/8" DXF™	H Omega™ DXM™

PHYSICAL DATA/
FOOTNOTES

ASTM E1264 Classification
Type III, Form 2, pattern C, E

ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 50

Imperial Weight
0.83-0.85 lb./ft²
Metric Weight
4.08-4.18 kg/m²

Thermal Resistance
R-1.7

Backloading
Refer to Installation and Maintenance

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Footnotes
1. For details, see LEED report tool at usgdesignstudio.com.
2. LR values are shown as averages.
3. Not all panel sizes available in all geographic areas, some metric sizes available to order.

Short Specification:

- Ceiling system shall comprise USG GALAXY Pin™ high humidity / fire resistant acoustical ceiling panels in (DONN Centricitee 15mm [9/16"] / DONN DX 24mm [15/16"] / DONN Omega 14mm [9/16"] / DONN Fineline 15mm [9/16"] / DONN Identitee 15mm [9/16"]) exposed grid including wall trim as manufactured by USG Interiors, LLC.
- Panels shall have NRC 0.55.
- Panels shall have CAC 33-35.
- Edge detail shall be (Shadowline Tapered [SLT] / Square Edge [SQ]).
- Limiting Conditions - Maximum 49°C (120°F)/99% RH.